



The Motor Ladder

SPECIFICATIONS:



Motor Ladder 21', 24' and 35'

The Ultra-Lite Motor Ladder is the low cost way to move materials, featuring continuous running belts that deliver payload every 6 seconds. Ideal for shingle, plywood, panels and other applications.

Ladder

Extension ladder:	Aluminum
Operating length:	15/21, 18/24 and 26/35 feet*
Transport length:	14, 16 and 20 feet
Width:	17 inches
Weight:	60, 65 or 95 lbs.
Belt rollers:	UHMW plastic
Drive belt:	Polyester webbing
Belt cleat:	3" high heat treated T-6 aluminum cleat
Distance between belts:	11 inches

**Ladders can be operated at two different lengths. Extension belt is included.*

Power Unit

115 volt motor, 3/4 hp., A.C. single phase forward and reverse
Transmission Speed reducer 30:1 mounted on motor
Weight is 40 lbs.

Optional Equipment

12 volt D.C., 1/2 hp electric motor with mounted 30 feet heavy duty cord with battery clamps.
(To use power through 12 volt truck battery)
Max Amp. Draw 38 Amp. Weight: 44 lbs.
Wireless Remote on-off control

Warranty: One year limited warranty

Have questions about the Motor Ladder?
Call and talk to us direct or email us at sales@liftconveyor.com

1-800-225-0057