



# Conveyor Truck Attachment

## SPECIFICATIONS:



The Lift Conveyor Truck Attachment is a totally self-contained 2-pc. unit that can be installed on any flatbed 10' or longer. To transfer Truck Attachment from one truck bed to another normally takes about 15 minutes. This unit features full 360° rotation (indexed every 30°), 3-ton hydraulic boom jack with spring loaded valve and operates at inclines up to 65°.



### All sizes

<b>Material:</b>	Powder coated steel
<b>Weight:</b>	350 lbs.
<b>Width:</b>	24"
<b>Height:</b>	63 inches with mounted conveyor in transport position
<b>Max inclination:</b>	65 degrees
<b>Extends behind truck bed:</b>	3 feet with mounted conveyor
<b>Rotation:</b>	360 degrees manual rotation
<b>Rotation brake:</b>	Spring loaded foot bar
<b>Leveling devise:</b>	Manual, t-handle adjustment
<b>Headboard saddle bracket:</b>	Made from steel with rubber lining
<b>Warranty:</b>	One year limited warranty



### Installation

- Mount frame in Stake Pockets
- Drop Rotator unit into Mount Frame
- Mount Boom & Cylinders
- Ready to mount Conveyor

Have questions about the Conveyor Truck Attachment?  
Call and talk to us direct or email us at [sales@liftconveyor.com](mailto:sales@liftconveyor.com)

**1-800-225-0057**