



The Motor Ladder

SPECIFICATIONS:



Motor Ladder 21', 24', and 28'

The Ultra-Lite Motor Ladder is the low cost way to move materials, featuring continuous running belts that deliver payload every 6 seconds. Ideal for shingles, plywood, panels, and other applications.

Ladder	
Extension Ladder:	Aluminum
Operating Length:	21', 24', and 28'
Transport Length:	14', 16', and 20'
Width:	17 inches
Weight:	60, 65, or 95 pounds
Belt Rollers:	UHMW plastic
Drive Belt:	Polyester Webbing
Belt Cleat:	3" high heat treated T-6 aluminum cleat
Distance between belts:	11 inches

**Ladders can be operated at two different lengths. Extension belt is included.*

Power Unit

115 volt motor, 3/4hp., A.C. single phase forward and reverse
Transmission Speed reducer 30:1 mounted on motor
Weight is 40lbs.

Table

Material:	Aluminum
Width:	20 inches
Height:	13 inches

Optional

12 volt D.C., 1/2 hp electric motor with mounted 30 feet heavy duty cord with battery clamps. (To use power through 12 volt truck battery)
Max Amp. Draw 38 Amp. Weight: 44lbs
Wireless Remote on-off control

Warranty:	One year limited warranty
------------------	---------------------------

Have questions about the Motor Ladder?
Call and talk to us direct or email us at sales@liftconveyor.com

1-800-225-0057

www.liftconveyor.com